

- 2"X4" FRAME PLAN GEOTEXTILE OVER WIRE MESH BACKING COMPACT BACK FILL AROUND INLET -CATCH BASIN INLET PROTECTION DETAIL

TEMPORARY SEEDING SEPCIFICATIONS SEEDING DATES LB./1000 FT. PER AC. SPECIES 4 BUSHEL MARCH 1 TO AUGUST 15 OATS 40 LB. TALL FESCUE 4 40 LB. ANNUAL RYEGRASS 1 PERENNIAL RYEGRASS 1 40 LB. 40 LB. TALL FESCUE 1 40 LB. ANNUAL RYEGRASS 1 3 2 BUSHEL AUGUST 16 TO NOVEMBER 1 RYE 4 40 LB. TALL FESCUE ANNUAL RYEGRASS 4 40 I B 2 BUSHEL WHEAT 3 1 40 LB. TALL FESCUE 40 LB. ANNUAL RYEGRASS 1 40 LB. PERENNIAL RYEGRASS 1 40 LB. TALL FESCUE ANNUAL RYEGRASS 40 LB. NOVEMBER 1 TO SPRING SEEDING USE MULCH ONLY, SODDING PRACTICES OR DORMANT SEEDING.

NOTE: OTHER APPROVED SEED SPECIES MAY BE SUBSTITUTED.

INGRESS-EGRESS
A STONE ACCESS DRIVE COMPLETE WITH UNDER LYING GEO-TEXTILE FABRIC (20 FEET WIDE AND 50 FEET LONG OR UPTO FRONT SETBACK) FOR INGRESS AND EGRESS AT THE SITE SHALL BE INSTALLED. THIS DRIVE SHALL BE THE ONLY ENTRANCE AND EXIT TO THE SITE.

STREETS DIRECTLY ADJACENT TO THE CONSTRUCTION ENTRANCES AND RECEIVING TRAFFIC FROM THE DEVELOPMENT AREA, SHALL BE CLEANED DAILY TO REMOVE SEDIMENT TRACKED OFF-SITE, IF APPLICABLE THE CATCH BASINS ON THESE STREETS NEAREST TO THE CONSTRUCTION ENTRANCES SHALL BE CLEANED

ALL SILT FENCE/ SOCK SHALL BE INSTALLED PRIOR TO ANY EARTHWORK ACTIVITIES AT THE SITE IN THE LOCATIONS SHOWN ON THE SITE PLAN AS WELL AS ALONG THE FRONT OF ANY LOT THAT SLOPES TOWARDS THE STREET.

DISTURBED AREAS OF THE SITE THAT ARE TO REMAIN IDLE FOR MORE THAN FOURTEEN (14) DAYS SHALL BE PROPERLY SEEDED AND STRAW MULCHED WITHIN SEVEN (7) DAYS OF COMPLETION OF INITIAL GRADING, TEMPORARY SEEDING AND MULCHING OF A THIRTY (30) FOOT STRIP OF THE ENTIRE FRONT OF THE LOT SHALL BE MAINTAINED ON THE SITE ONCE INITIAL GRADING IS COMPLETE.

STABILIZATION OF CRITICAL AREAS WITHIN FIFTY (50) FEET OF ANY STREAM OR WETLAND SHALL BE COMPLETE WITHIN TWO (2) DAYS OF THE DISTURBANCE IF THE SITE IS TO REMAIN INACTIVE FOR LONGER THAN FOURTEEN (14) DAYS.

STRAW-MULCH SHALL BE APPLIED AT A RATE OF 1 BALE PER EVERY TEN (10) FEET OF CURB, AT A WIDTH OF THIRTY (30) FEET OF THE ENTIRE LENGTH OF THE LOT. WOOD CHIPS MAY ALSO BE USED BUT MUST BE SPREAD AT A MINIMUM DEPTH OF FOUR INCHES OVER THE THIRTY FOOT WIDTH AND MUST BE ACCOMPANIED BY A PROPERLY INSTALLED SILT FENCE.

EROSION AND SEDIMENT CONTROLS SHALL BE INSPECTED EVERY SEVEN (7) DAYS OR WITHIN 24 HOURS OF A 0.5" OR GREATER RAINFALL EVENT. NECESSARY REPAIRS SHALL BE MADE AT THIS TIME,

ALL EROSION AND SEDIMENT CONTROL SPECIFICATIONS, APPLICATIONS, AND TIMETABLES ARE BASED OF THE DESCRIPTIONS AND STANDARDS OF THE OHIO DEPARTMENT OF NATURAL RESOURCES "RAINWATER AND LAND DEVELOPMENT MANUAL" AND CAN BE FOUND IN THE LAKE COUNTY EROSION AND SEDIMENT CONTROL RULES AS ADOPTED DECEMBER 21, 1999.

THE SPECIFIED EROSION AND SEDIMENT CONTROL STANDARDS ARE GENERAL GUIDELINES AND SHALL NOT LIMIT THE RIGHT OF THE COUNTY TO IMPOSE, AT ANY TIME, ADDITIONAL, MORE EROSION CONTROL PRACTICES.

HUF. 10 FT, MINIMUM AND NOT LESS THAN SECTION ROAD OR OTHER **PLAN VIEW** RIGHT OF WAY DIVERSION PAVED SURFACE AS NEEDED BACKFILLED COMPACTED 18" OR SUFFICIENT PROFILE SECTIONS SILT FENCE DETAIL CONSTRUCTION ENTRANCE DETAIL

INLET PROTECTION NOTES:

- 1. WHERE MINIMUM CLEARANCES CAUSE TRAFFIC TO DRIVE IN THE GUTTER, THE CONTRACTOR MAY SUBSTITUTE A 1" X 4" BOARD SECURED WITH CONCRETE NAILS 3" O.C. NAILED INTO THE GUTTER IN LIEU OF SANDBAGS TO HOLD THE FILTER DIKE IN PLACE. UPON REMOVAL, CLEAN ANY DIRT/DEBRIS FROM NAILING LOCATIONS, APPLY CHEMICAL SANDING AGENT AND APPLY NON-SHRINK GROUT FLUSH WITH SURFACE OF GUTTER.
- 2. A SECTION OF FILTER FABRIC SHALL BE REMOVED AS SHOWN ON THIS DETAIL OR AS DIRECTED BY THE ENGINEER OR DESIGNATED REPRESENTATIVE. FABRIC MUST BE SECURED TO WIRE BACKING WITH CLIPS OR HOG RINGS AT THIS LOCATION.
- 3. DAILY INSPECTION SHALL BE MADE BY THE CONTRACTOR AND SILT ACCUMULATION MUST BE REMOVED WHEN DEPTH REACHES 2".
- 4. CONTRACTOR SHALL MONITOR THE PERFORMANCE OF INLET PROTECTION DURING EACH RAINFALL EVENT AND IMMEDIATELY REMOVE THE INLET PROTECTIONS IF THE STORM-WATER BEGINS TO OVERTOP THE CURB.
- 5. INLET PROTECTIONS SHALL BE REMOVED AS SOON AS THE SOURCE OF SEDIMENT IS STABILIZED.

	T						
6 -1 869 798 8798							
N. J. S.		48.5.20.45.16					
NO.	DATE		BY				
REVISIONS							

SUHAIL

18405 May Court, Chagrin Falls, Ohio 44023 Ph.: (800) 660-4291 Fax: (800) 660-7831

	DES. BY	ŤJ	
***************************************	ÇĤK. BY	FA	EROS
ľ	RE,CHK. BY	HS	LINUG
	APR.BY	ES	
***************************************	DATE	SEP. 18, 2014	
i	SCALE	AS NOTED	41141

SION & SEDIMENT CONTROL PLAN FOR S/L 15 ORCHARD SPRINGS

PREPARED FOR RYAN HOMES 6770 W. SNOWVILLE ROAD SUITE 100 BRECKSVILLE, OHIO-44141 (440) 584-4200 S&S JOB NO. SHEET NO.

20140101 2 OF 2